

## Qualified Vendors List (QVL) Standard table for user manual

Project Name: A8N-SLI

Size	Vendor	Model	CL	Brand	SS/DS	Component	DIMM socket support (Optional)		
							A*	B*	C*
256MB	KINGSTON	KVR400X64C3A/256	N/A	Hynix	SS	HY5DU56822BT-D43	V	V	V
512MB	KINGSTON	KVR400X64C3A/512	N/A	Hynix	DS	HY5DU56822BT-D43	V	V	V
256MB	KINGSTON	KVR400X72C3A/256	N/A	Mosel	SS	V58C2256804SAT5(ECC)	V	V	V
512MB	KINGSTON	KVR400X72C3A/512	N/A	Mosel	DS	V58C2256804SAT5(ECC)	V		V
256MB	KINGSTON	KVR400X64C3A/256	N/A	Infineon	SS	HYB25D256800BT-5B	V	V	V
512MB	KINGSTON	KVR400X64C3A/512	N/A	Infineon	DS	HYB25D256809BT-5B	V	V	
256MB	KINGSTON	KVR400X64C3A/256	N/A	KINGSTON	SS	D3208DL2T-5	V	V	V
512MB	KINGSTON	KVR400X64C3A/512	N/A	KINGSTON	DS	D328DIB-50	V	V	V
1024MB	KINGSTON	HYB25D512800BE-5B	3	N/A	DS	KVR400X64C3A/1G	V	V	V
256MB	SAMSUNG	M381L3223ETM-CCC	3ECC	SAMSUNG	SS	K4H560838E-TCCC(ECC)	V	V	V
512MB	SAMSUNG	M381L6423ETM-CCC	N/A	SAMSUNG	DS	K4H560838E-TCCC(ECC)			V
256MB	SAMSUNG	M368L3223ETM-CCC	N/A	SAMSUNG	SS	K4H560838E-TCCC	V	V	V
256MB	SAMSUNG	M368L3223FTN-CCC	4	SAMSUNG	SS	K4H560838F-TCCC	V	V	V
512MB	SAMSUNG	M368L6423FTN-CCC	4	SAMSUNG	DS	K4H560838F-TCCC	V	V	V
512MB	SAMSUNG	M368L6523BTM-CCC	4	SAMSUNG	SS	K4H510838B-TCCC	V	V	V
256MB	MICRON	MT8VDDT3264AG-40BCB	N/A	MICRON	SS	MT46V32M8TG-5BC	V	V	V
512MB	MICRON	MT16VDDT6464AG-40BCB	N/A	MICRON	DS	MT46V32M8TG-5BC	V	V	V
256MB	Infineon	HYS64D32300HU-5-C	3	Infineon	SS	HYB25D256800CE-5C	V	V	V
512MB	Infineon	HYS64D64320HU-5-C	N/A	Infineon	DS	HYB25D256800CE-5C	V	V	V
256MB	CORSAIR	CMX256A-3200C2PT	2	Winbond	SS	W942508BH-5	V	V	V
512MB	CORSAIR	VS512MB400	2.5	VALUE seLecT	DS	VS32M8-5	V		V
1024MB	CORSAIR	TWINX2048-3200C2	3	N/A	DS	N/A	V	V	
256MB	Hynix	HYMD232645D8J-D43	3	Hynix	SS	HY5DU56822DT-D43	V	V	V
512MB	Hynix	HYMD264646D8J-D43	3	Hynix	DS	HY5DU56822DT-D43	V	V	V

Note:

A\* : Supports one module inserted in any slot as Single-channel memory configuration

B\* : Supports one pair of modules inserted into either the blue slots or the black slots as one pair of Dual-channel memory configuration

C\* : Supports 4 modules inserted into both the blue and black slots as two pairs of Dual-channel memory configuration